

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/035198 A1

- (51) International Patent Classification⁷: **B01J 8/02** (74) Agent: ZARDI, Marco; M. Zardi & Co. S.A., Via Pioda, 6, CH-6900 Lugano (CH).
- (21) International Application Number: PCT/EP2003/009931 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 8 September 2003 (08.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 02023316.9 17 October 2002 (17.10.2002) EP (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (*for all designated States except US*): AMMONIA CASALE S.A. [CH/CH]; Via Sorengo, 7, CH-6900 Lugano-Besso (CH).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): FILIPPI, Ermanno [IT/CH]; Strada di Gandria, 73, CH-6976 Castagnola (CH). RIZZI, Enrico [IT/IT]; Via Montale, 10, I-22070 Grandate (IT). TAROZZO, Mirco [IT/CH]; Via L. Piffaretti, CH-6853 Ligornetto (CH). CLAYTON, Keith, A. [CA/US]; Nr Strathmore, Alberta CA T1P 1JP (US).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: METHOD TO CARRY OUT STRONGLY EXOTHERMIC OXIDIZING REACTIONS IN PSEUDO-ISOTHERMAL CONDITIONS

(57) Abstract: Method and apparatus for carrying out highly exothermic catalyzed reactions, like so-called oxidative reactions, in pseudo-isothermal conditions, for example the reaction for producing nitric acid and the reaction for producing formaldehyde. At least part of the continuous flow of reactants is fed at different points of the catalytic bed corresponding to different successive stages of the reaction.

Title: "Method to carry out strongly exothermic oxidizing reactions in pseudo-isothermal conditions"

DESCRIPTION

Field of the invention

5 In its most general aspect the present invention refers to a method for carrying out exothermic chemical reactions in pseudo-isothermal conditions.

In the rest of the description and in the subsequent claims, with the term pseudo-isothermal conditions we mean
10 to indicate those conditions in which the reaction temperature is controlled in a limited range of values around a predetermined optimal value.

In particular, this invention concerns a method for carrying out, in pseudo-isothermal conditions, highly
15 exothermic catalyzed reactions, like oxidative reactions, for example ammonia oxidation to give nitric acid and methanol oxidation to give formaldehyde.

The present invention also refers to an apparatus for carrying out the aforementioned method.

20 Prior Art

Regarding highly exothermic oxidative reactions it is well known that, in order to avoid clearly dangerous operating conditions, it is required to control one or more operating variables, like reaction temperature and concentration of
25 at least one reactant.

Thus, for example, in the production of formaldehyde through methanol oxidation, the high concentration of the

reactants and the high exothermicity of the reaction quickly lead to operate in explosive conditions; from here arises the need to strictly control both the concentration of the reactants and the reaction temperature below well-determined values.

Moreover, when the reaction temperature and concentration of the reactants exceed said values, there may happen phenomena of "poisoning" and degeneration of the catalyst, with the consequent inevitable yield reduction. This is the case of ammonia oxidation to give nitric acid, where the catalyst based upon Co_3O_4 undergoes a rapid CoO reduction, a much less active form of Co_3O_4 , right when the concentration of the reactant exceeds a predetermined threshold at a predetermined temperature.

To control the temperature and the concentration of the reactants, it has been suggested to carry out the reactions of the considered type in fluid bed reactors.

This type of reactor, however, suffers from many recognized drawbacks, such as excessive energy consumption caused by the need to feed large quantities of air so as to keep the ammonia concentration below the explosivity threshold, greater constructive complexity with respect to fixed bed reactors and problems of dust recovery.

Moreover, the catalyst in movement inside said fluid bed reactors carries out a corrosive action against the walls of the reactors themselves.

Summary of the invention

The technical problem underlying the present invention is that of providing a method for carrying out highly

exothermic oxidative reactions, in pseudo-isothermal conditions, between reactants fed in continuous flow to a predetermined catalytic bed, capable of overcoming the aforementioned drawbacks with reference to the prior art, in other words to operate below explosivity limits of the mixtures of reactants and of reactants-products and to promote a longer lifetime of the catalyst.

The aforementioned technical problem is solved, according to the present invention, by a method characterized in that at least part of said continuous flow of reactants is fed at different points of said catalytic bed corresponding to different successive stages of the reaction, at respective different predetermined temperatures and flow-rates, where the concentration of the reactants is low.

In the non-limiting case of use of a pseudo-isothermal reactor with a vertical axis, with a catalytic bed crossed axially by the reactants, the successive stages of the reaction are defined at different respective heights in the catalytic bed, wherein the reactants are fed at the predetermined flow-rates and temperatures.

The characteristics and advantages of the method of the present invention shall become clearer from the following description of an example embodiment thereof, made with reference to the attached drawings given for indicating and not limiting purposes.

Brief description of the drawings

Figure 1 schematically shows a chemical reactor for carrying out the method according to the invention;

Figure 2 schematically shows an enlarged view of a detail of the reactor of figure 1.

Detailed description of the figures

With reference to figure 1, a chemical reactor, with a vertical axis, used to carry out highly exothermic reactions, for example and preferably oxidative reactions like ammonia oxidation to give nitric acid, is globally and schematically indicated with 1.

Said reactor 1 comprises a cylindrical shell 2, opposite end plates, lower 3 and upper 4. The upper end plate 4 is equipped with a manhole 5, whereas the lower end plate 3 is equipped with an opening 6 for discharging the reaction products.

In said shell 2 a reaction zone 7 is defined, representatively situated between a lower line 8 and an upper line 9, to receive a predetermined catalytic bed (L), intended to be crossed axially by the reactant gases and by the reaction products.

The catalytic bed (L) is supported in a per se known way and therefore it is not represented.

In the catalytic bed (L) a plurality of heat exchangers 10 and a corresponding plurality of distribution-supplier devices 12 are immersed and supported; said heat exchangers 10 are plate-shaped, rectangular, preferably arranged radially, in many rows concentric and coaxial to said shell and with long sides 11 parallel to the axis of the shell itself.

In accordance with a characteristic of the present invention, and according to a preferred embodiment, with

each exchanger 10 is associated, in particular is fixed, a couple of distribution-suppliers 12, for which it constitutes an appropriate support, as shall become clear from the rest of the description.

- 5 In particular, with reference to figure 2, each heat exchanger 10 comprises a wall 27 and a wall 28, juxtaposed, joined at the perimeter, for example through appropriate welding, in a mutually distanced relationship, so as to form a first chamber 18 between them.
- 10 Near to a side 11 of said exchanger 1 and through a welding line 25, having a portion 32 parallel to said side 11 and a portion 33 perpendicular to it, between said walls 27 and 28 a second chamber 19 is also defined, separated fluid-tight from said first chamber 18.
- 15 The chamber 18 is equipped with an inlet fitting 29, and with an outlet fitting 31, whereas the chamber 19 comprises only one inlet fitting 34.

Two box-shaped carters 20 and 22 are fixed to the wall 27 of each exchanger 10, extending perpendicularly to said
20 side 1 for the whole width of the respective exchanger 10.

The carters 20 and 22 define with the wall 27 respective ducts 21 and 23, in fluid communication, on one side, with said second chamber 18 through openings 36 and 37, formed in the wall 27 and, on the other side, with the outside of
25 the exchanger 10, and therefore with the catalytic bed (L) in which said exchanger 10 is immersed, through a plurality of holes 26, formed in the carters themselves.

Preferably, said holes 26 are arranged in rectilinear alignments, extending longitudinally to the respective carter (20, 22).

5 The carters 20 and 22, supported by a respective exchanger 10, essentially constitute a distribution-supplier device 12 for a predetermined fluid, fed to said carters through the chamber 18.

10 The plurality of exchangers 10 with relative distribution-suppliers 12, constitutes, in accordance with the present invention, an apparatus suitable for controlling the temperature and the concentration of the reactants in the catalytic bed (L), as shall become clear in the rest of the description.

The reactor 1 also comprises:

- 15 - feed ducts for the predetermined reactants (13 and 14) which are in fluid communication with the chamber 18 and 19 respectively of each exchanger 10, through a system which includes ducts (15 and 16) and respective fittings (30 and 35).
- 20 - collector ducts 17 for the reaction products, which are in fluid communication, on one side, with the outlet fittings 31 of each exchanger and, on the other side, with a central duct 24 axially provided in the reactor.

25 With reference to the aforementioned apparatus, the method of the present invention for carrying out highly exothermic oxidative reactions in pseudo-isothermal conditions, through simultaneous control of the reaction temperature and of the concentration of reactants around respective predetermined values, shall now be described.

A flow of reactants, for example ammonia and oxygen for the production of nitric acid, is continuously fed to the reactor 1, and is separated into two parts upon entry.

5 A first part or main part of said flow is preheated to the most appropriate temperature to trigger the desired reaction (ammonia oxidation) through heat exchange with the catalytic bed (L); for such a purpose and in the specific case illustrated, said main part of the flow of reactants is divided, through the distributor 12, between all of the
10 ducts 15 - fittings 30, for feeding the chambers 18 of all of the exchangers 10.

Exiting from the plurality of exchangers 10, the reactants thus preheated are collected by the collector 20, which conveys them to the lower end of the central duct 24.
15 Exiting from the upper end of said duct 24, the preheated reactants are distributed above the catalytic bed (L), crossing which they start off the desired highly exothermic oxidation reaction.

A second part of said flow of reactants, or control flow,
20 is divided between all the chambers 18 of the plurality of exchangers 10, from each of which it is fed to the respective pairs of distribution-suppliers 19, 20.

As described above, said distribution-suppliers 19, 20 are positioned in the catalytic mass of the bed (L), at heights
25 strictly corresponding to the stages of the reaction taking place in correspondence of which it is foreseen to control the concentration and temperature of the reactants.

In accordance with the present invention such a control is substantially made possible by the injection in
30 predetermined points of the catalytic bed of a fresh flow

of reactants, the concentration of which is regulated continuously adjusting suitably and in a per se known way the flow rate of the second part of said flow of reactants.

The reaction products are discharged from the reactor 1
5 through the opening 6.

The invention thus conceived is susceptible to variants and modifications, all of which are covered by the scope of protection of the present invention defined by the following claims.

CLAIMS

1. Method for carrying out highly exothermic oxidative reactions in pseudo-isothermal conditions, between reactants fed in continuous flow to a predetermined catalytic bed, characterized in that at least a part of said continuous flow of reactants is fed at different points of said catalytic bed corresponding to different successive stages of the reaction, at respective different predetermined temperatures and flow-rates.
2. Method for carrying out highly exothermic oxidative reactions in pseudo-isothermal conditions, between reactants fed in a continuous flow to a predetermined catalytic bed (L), in which a plurality of heat exchangers (10) is immersed and supported, characterized in that:
- a plurality of distribution-suppliers (20, 22) is positioned in said catalytic bed (L), at different points thereof strictly corresponding to different predetermined stages of said oxidative reaction,
 - said continuous flow of reactants is divided into a first part or main flow and a second part or control flow with a predetermined temperature and flow-rate,
 - said first part or main flow is preheated through heat exchange with said catalytic bed (L), feeding it through said plurality of exchangers (10),
 - said main flow of preheated reactants is recovered and it is fed continuously to said catalytic bed (L),
 - said second part or control flow is fed to said plurality of distribution-suppliers (20, 22) to inject

respective fresh flows of reactants at a predetermined temperature and flow-rate into the catalytic bed (L).

3. Apparatus for carrying out a highly exothermic oxidative reaction in pseudo-isothermal conditions according to the method of claims 1 and 2, comprising a plurality of heat exchangers (10), characterized in that with each of said exchangers is associated at least one distribution-supplier (20, 22) suitable for being fed continuously by a flow of reactants at a predetermined temperature and flow-rate.

4. Apparatus according to claim 3, characterized in that said at least one distribution-supplier (20, 22) is supported fixed by said respective heat exchanger (10).

5. Apparatus according to claim 4, characterized in that said heat exchanger (10) is plate-shaped and substantially rectangular, inside which a first chamber (18), intended to be crossed by a respective flow of reactants to be preheated, and a second chamber (19), separated fluid-tight from said first chamber (18) and in fluid communication with said at least one distribution-supplier (20, 22) are defined.

6. Apparatus according to claim 5, characterized in that said distribution-supplier (20, 22) comprises a carter fixed to a wall of a respective plate-shaped heat exchanger (10), with which it substantially defines a duct in fluid communication, on one side, with said second chamber (19) of the exchanger (10) and, on the other side, with the outside of the exchanger (10) itself, through a plurality of holes formed in said carter.

7. Reactor for carrying out highly exothermic catalyzed
oxidative reactions in pseudo-isothermal conditions,
comprising a shell in which is defined a reaction zone at
least partially occupied by a catalytic bed (L),
5 characterized in that it comprises an apparatus according
to claims 3 to 6, immersed in said catalytic bed (L).




Fig. 1

2/2




Fig. 2

INTERNATIONAL SEARCH REPORT

National Application No
PCT/EP 03/09931

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B01J8/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B01J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR 2 029 533 A (BASF AG) 23 October 1970 (1970-10-23)	1
Y	claims 1-3; figure 2; example 2	2
Y	EP 1 236 505 A (METHANOL CASALE SA) 4 September 2002 (2002-09-04) claims 1-6; figure 4	2
A	GB 680 605 A (CALIFORNIA RESEARCH CORP) 8 October 1952 (1952-10-08) the whole document	1
A	US 6 153 149 A (FLOUDAS CHRISTODOULOS A ET AL) 28 November 2000 (2000-11-28) claims 1-31; figures 1,2	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

28 January 2004

Date of mailing of the international search report

06/02/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Cubas Alcaraz, J

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 03/09931

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2029533	A	23-10-1970	DE 1904078 A1 BE 744980 A1 FR 2029533 A5 NL 7000999 A	13-08-1970 27-07-1970 23-10-1970 30-07-1970
EP 1236505	A	04-09-2002	EP 1236505 A1 CA 2438662 A1 WO 02068110 A1 EP 1363729 A1 US 2002117294 A1	04-09-2002 06-09-2002 06-09-2002 26-11-2003 29-08-2002
GB 680605	A	08-10-1952	NONE	
US 6153149	A	28-11-2000	NONE	